



**DYNA**



**HINO**


A Toyota Group Company



## THE DYNA MADE FOR THE CITY

GET AROUND THE CITY WITH EASE IN THE IDEAL CITY LOGISTICS VEHICLE, the nimble Dyna. Fitted with the proven 5L engine, it delivers high power and torque and its handling capabilities make operations in and around the city a breeze.





TOYOTA DYNA SPECIFICATIONS	
DIMENSIONS (mm)	CHASSIS CAB
OL – Overall length	4 690
WB – Wheelbase	2 545
FOH – Front overhang	960
ROH – Rear overhang	1 010
BBC – Bumper to back of cab	1 479
CA – Cab to axle	2 025
OVH – Overall vehicle height	1 980
FW – Frame outside width at engine	745
FH – Frame height (rear)	700
FT – Front track	1 435
RT – Rear track	1 500
MGC – Min ground clearance	200
WARW – Width across rear wheels	1 900
<b>Homologated body width</b>	
- Minimum	1 920
- Maximum	2 100
<b>Body Length</b>	
Suggested body length (Exterior)	2 950
Maximum body length (Exterior)	3 500
MASS DATA	CHASSIS CAB
<b>Tare</b>	
Front	1 040
Rear	580
Total	1 620
<b>GA</b>	
Front	1 800
Rear	2 550
<b>A</b>	
Front	1 800
Rear	2 550
GVM	3 500
<b>V-Rating</b>	
GCM – D/T	4 300
Approx. body/payload	1 880

TOYOTA DYNA	
SPECIFICATIONS	CHASSIS CAB
<b>Engine</b>	
Type	5L
Type	4 cyl in-line
Displacement (cm <sup>3</sup> )	2 986
No. of valves per cylinder	2
Aspiration	Natural
Emission status	Euro 2
<b>Performance (sea level)</b>	
Gradeability @ GVM (%)	35
Max. geared speed (km/h)	127
Air cleaner	Toyota
Power (kW @ r/min)	67 @ 4 000
Torque (Nm @ r/min)	192 @ 2 400
<b>Transmission</b>	
Model	R452
Type	5-Speed Synchro
Ratio	5.146 – 0.830
<b>Clutch</b>	
Diameter (mm)	236
<b>Rear Axle</b>	
Type	Hypoid Single Reduction
Ratio	4.300:1
<b>Steering</b>	
	Power assisted
<b>Suspension</b>	
Rear	
- Type	Semi-elliptic leaf
- Shock absorbers	Double acting
Front	
- Type	Double wishbone torsion bar
- Configuration	Independent
- Shock absorbers	Double acting
<b>Brakes</b>	
System	Hyd/Vac assist
Type front	Disc
Type rear	Drum
ABS	Yes
<b>Wheels &amp; Tyres</b>	
Wheel size	15 x 5J
Tyre size	195/70R15C
Load/Speed rating	104/102 S
Spare wheel carrier	Yes
<b>Other Specifications</b>	
Fuel tank capacity (litres)	80
Electrical system	12 Volt, Neg.
<b>Service Intervals (km)</b>	
On-road application	10 000 km
WARRANTY	
Vehicle	12 months, unlimited km
Driveline	24 months, 150 000 km
Rust Perforation	36 months, unlimited km



Date: 01/2017 Part No. DYNASP Waste Tyre Reg No. TPREG0031GAU

Certain vehicle details and specifications contained in this leaflet may differ from the available models. Hino Motors limited and Hino South Africa reserves the right to alter any details of specifications and equipment without notice. For the most current information on prices and specifications, as well as comprehensive information about products offered by Hino, contact your dealer, or Hino South Africa. Call 0800 139 111 or visit [www.hino.co.za](http://www.hino.co.za)

