

specifications

	Models ⁽¹⁾	Kilowatts ⁽²⁾	Max. RPM at Full Throttle	Cylinders	Displacement	Starting	Gear Ratio	Gear Shift	Steering
MERCURY VERADO									
300-225	NEW Verado 300 • Verado 250 • Verado 225	221 • 183 • 165 kW	5800-6400	6 (in-line)	2598 cc	Electric (turn-key)	300: 1.75:1 250 • 225: 1.85:1	Forward (F) - Neutral (N) - Reverse (R)	Electro-hydraulic Power steering with integral hydraulic cylinder
200-135	NEW Verado 200 • Verado 175 • Verado 150 • Verado 135	147 • 129 • 110 • 99.2 kW	200 • 175 • 150: 5800-6400 135: 5200-6400	4 (in-line)	1732 cc	Electric (turn-key)	2.08:1	Forward (F) - Neutral (N) - Reverse (R)	Remote
MERCURY FOURSTROKE									
115-80	115 EFI • 100 EFI • 80 EFI	84.5 • 73.5 • 58.8 kW	115: 5800-6400 100 • 80: 5000-6000	4 (in-line)	1732 cc	Electric (turn-key)	115: 2.07:1 100 • 80: 2.33:1	Forward (F) - Neutral (N) - Reverse (R)	Remote
60-40	60 EFI • BIGFOOT • 50 EFI	44.1 • 36.8 kW	5500-6000	4 (in-line)	995 cc	Electric (turn-key)	1.83:1 BIGFOOT: 2.33:1	Forward (F) - Neutral (N) - Reverse (R)	Remote
	40 EFI	29.4 kW	5500-6000	3 (in-line)	747 cc	Electric (turn-key)	2.00:1	Forward (F) - Neutral (N) - Reverse (R)	Remote
30-25	30 EFI • 25 EFI	22.1 • 18.4 kW	30: 5250-6250 25: 5000-6000	3 (in-line)	526 cc	Manual or Electric (turn-key)	1.92:1	Forward (F) - Neutral (N) - Reverse (R)	Tiller or Remote
20	NEW 20	14.7 kW	5000-6000	2 (in-line)	351 cc	Manual or Electric	2.15:1	Forward (F) - Neutral (N) - Reverse (R)	Tiller or Remote
15-8	15	11 kW	4500-5500	2 (in-line)	323 cc	Manual or Electric	2.00:1	Forward (F) - Neutral (N) - Reverse (R)	Tiller or Remote
	9.9 • 8	7.3 • 5.9 kW	5000-6000	2 (in-line)	209 cc	Manual or Electric	2.08:1	Forward (F) - Neutral (N) - Reverse (R)	9.9: Tiller or Remote 8: Tiller
6-2.5	6 • 5 • 4 • SAILPOWER	4.4 • 3.68 • 2.9 kW	6: 5000-6000 5 • 4: 4500-5500	1	123 cc	Manual	2.15:1	Forward (F) - Neutral (N) - Reverse (R)	Tiller
	3.5 • 2.5	2.6 • 1.8 kW	5000-6000	1	85 cc	Manual	2.15:1	Forward (F) - Neutral (N)	Tiller
MERCURY OPTIMAX									
225-135	225 • 200 OptiMax	165 • 147 kW	5000-5750	V-6 (60° Vee)	3032 cc	Electric (turn-key)	1.75:1	Forward (F) - Neutral (N) - Reverse (R)	Remote
	175 • 150 • 135 OptiMax	129 • 110 • 99.2 kW	175 • 150: 5250-5750 135: 5000-5600	V-6 (60° Vee)	2507 cc	Electric (turn-key)	175 • 150: 1.87:1 135: 2.00:1	Forward (F) - Neutral (N) - Reverse (R)	Remote
115-75	115 • 90 • 75 OptiMax	84.5 • 66.2 • 55.1 kW	5000-5750	3 (in-line)	1526 cc	Electric (turn-key)	115: 2.07:1 90 • 75: 2.33:1	Forward (F) - Neutral (N) - Reverse (R)	Remote

For more information on the propeller that is right for you, please see your dealer.