


Alternator System ⁽¹⁾	Trim Positions	Fuel Tank	Fuel Requirements	Weight ⁽⁴⁾	Recommended Boat Transom Height	Induction System	Counter Rotation
Fully regulated Belt-Driven 70 amp (882 watt)	SmartCraft-programmable Power trim and tilt	Optional	Verado 300: Unleaded 98 RON recommended for maximum performance Verado 250 • 225: Unleaded 90 RON min.	288 kg	508 mm (L) - 635 mm (XL) - 762 mm (XXL)	SmartCraft DTS (Digital Throttle & Shift), supercharged with charge air cooling and electronic boost pressure control	Available on XL and XXL models
Fully regulated Belt-Driven 70 amp (882 watt)	Power trim and tilt with SmartCraft-programmable tilt	Optional	Unleaded 90 RON min.	231 kg	508 mm (L) - 635 mm (XL)	SmartCraft DTS (Digital Throttle & Shift), supercharged with charge air cooling and electronic boost pressure control	Available on XL models
Fully regulated Belt-Driven 50 amp (630 watt)	Power trim standard	Optional	Unleaded 90 RON min.	181 kg	115 • 100: 508 mm (L) - 635 mm (XL) 80: 508 mm (L)	4-valve dual overhead cam design	N/A
18 amp (223 watt)	Power trim standard	Standard 25 L	Unleaded 90 RON min.	112 kg BIGFOOT: 120 kg	508 mm (L)	2-valve single overhead cam design	N/A
18 amp (223 watt)	Gas assist and Power trim models available	Standard 25 L	Unleaded 90 RON min.	98 kg	381 mm (S) 508 mm (L)	2-valve single overhead cam design	N/A
15 amp (186 watt)	30: Gas assist or Power trim 25: Manual or Power trim	Standard 25 L	Unleaded 90 RON min.	30: 78 kg 25: 71 kg	381 mm (S) 508 mm (L)	2-valve single overhead cam design	N/A
11 amp (139 watt)	5 & shallow water drive	Standard 12 L	Unleaded 90 RON min.	51.6 kg	381 mm (S) 508 mm (L)	2-valve single overhead cam design	N/A
Manual 6 amp (76 watt) Electric 10 amp (126 watt)	5 & shallow water drive Standard: M, ML (Optional: E, EL)	Standard 12 L	Unleaded 90 RON min.	50 kg	381 mm (S) 508 mm (L)	2-valve single overhead cam design	N/A
6 amp (76 watt) on electric-start models	5 & shallow water drive	Standard 12 L	Unleaded 90 RON min.	38 kg	381 mm (S) 508 mm (L)	2-valve single overhead cam design	N/A
Optional 4 amp (50 watt) lighting, 2 amp (25 watt) charging 4 SAILPOWER: Standard with rectifier	6 & shallow water drive	6 • 5: Standard 12 L 4 + 4 SAILPOWER: Integrated fuel tank 1.1 litre	Unleaded 90 RON min.	25 kg	381 mm (S) 508 mm (L) 4 SAILPOWER: 508 mm (L)	2-valve pushrod	N/A
N/A	4	Integrated fuel tank 1.3 litre	Unleaded 90 RON min.	17 kg	3.5: 381 mm (S) 508 mm (L) 2.5: 381 mm (S)	2-valve pushrod	N/A
Belt-Driven 60 amp (756 watt)	Power trim standard	Optional	Unleaded 90 RON min.	225 kg	508 mm (L) - 635 mm (XL)	2-stage direct fuel injection	Available on XL models
Belt-Driven 60 amp (756 watt)	Power trim standard	Optional	Unleaded 90 RON min.	195 kg	508 mm (L) - 635 mm (XL)	2-stage direct fuel injection	Available on XL models
Belt-Driven 60 amp (756 watt)	Power trim standard	Optional	Unleaded 90 RON min.	170 kg	115: 508 mm (L) - 635 mm (XL) 90 • 75: 508 mm (L)	2-stage direct fuel injection	N/A

(1) Model offering may vary from one country to another. Please see your local dealer for specific information. (2) Measured at propshaft in accordance with ICOMIA 28.

(3) Requires rectifier to complete installation manual versions. Standard on 4 Sailpower model. (4) Dry weight specification is for lightest model and excludes engine oil, rigging hardware and propeller.

 SmartCraft Integrated Marine technology standard.